

## Vacuum Sealing Machine

**Model : DZ-4002S**



### Product Details :

- Double chambers vacuum packing machine can be used for middle or small products
- Two vacuum chamber working alternatively, efficient is high
- There are two types of electrical control system, relay automatic control system and computer automatic control system, its up to customer's need
- The inflation system is optional



บริษัท โพรเฟสชั่นแนล เซอร์วิส ยูไนเต็ด จำกัด

465 หมู่ที่ 3 ตำบลบ้านคลองสวน อำเภอพระสมุทรเจดีย์ จังหวัดสมุทรปราการ 10290

Tel. 0-2461-5764-5,0-16850402 Fax. 0-2461-5766 Email. [sales@psu.co.th](mailto:sales@psu.co.th)

---

**Technical Specification:**

<b>Model</b>	<b>DZ-400/2S</b>
Voltage (V/HZ)	AC 380/50 220/50 110/60
Vacuum pump motor power (KW)	0.75
Sealing power (W)	500
Ultimate vacuum (Kpa)	1
Sealing bar quantity/chamber	2
Sealing length (mm)	400
Sealing width (mm)	10
Product max. length (mm)	435
Chamber size (L*W*H)(mm)	445*500*45
Vacuum pump rate (m <sup>3</sup> /h)	20
Chamber material	Stainless steel
Machine weight (kg)	181
Machine size (L*W*H)(mm)	1160*740*1090