



Pallet wrapping machine Model : K1100



▶ Machine features :

- ☐ Totally enclosed Electrical cabinet, Avoid dust enter, which have long service life and lower problem.
- ☐ Protection level IP54, complying with CE standard.
- ☐ Which have origin start and random start function, It has been designed to meet all customer.
- ☐ New film frame design, The stretch effect of the winding film is more uniform and smooth.
- ☐ Special balance control round design, make the turntable reduce noise, easier to maintain.

▶ Main performance :

Control system

- ☐ Program-controlled unit all-in-one, The number of winding layers and times can be set;
- ☐ Photoelectric switch, Automatically sensing the height of the goods;
- ☐ Reinforcement winding function, Special protection may be made for certain parts;
- ☐ Top time setting function;
- ☐ Within switch protection device and emergency stop switch device;



Pallet wrapping machine Model : K1100

▶ The film frame system :

- ☐ The film frame is a-c dynamo Mechanical stretching mechanism, also has frequency control, adjust film tension, Mechanical stretching up to 300%;
- ☐ The film frame structure use integral welding technology and Laser positioning cutting process, The film frame higher strength and machining accuracy, Let the film frame more stable and lower noise;
- ☐ The film frame up, down speed, the film send speed Adjustable;
- ☐ Top and bottom winding numbers are individually controlled;
- ☐ Film system follow-move mechanism, just pull it;
- ☐ New film frame design, the stretch effect of the winding film is more uniform and smooth;
- ☐ Easy transportation and movement;

▶ Turntable drive :

- ☐ Turntable speed 0~12 rpm adjustable;
- ☐ The turntable drive is chain drive, accurate positioning;
- ☐ Automatic reset of turntable;

▶ Main technical parameters :

Turntable diameter	Ø1650 mm
Packing height	2400 mm
Wrapping specifications	L:600-1200 x W:500-1100 mm
Turntable height	78 mm
Turntable bearing	2000 kg
Power	1.5 kw
Supply voltage	Single-phase 220V
Rotary speed	0~12 r/min
Packaging	LLDPE Stretched film
Thickness	17~35 μm
Breadth	500 mm
Film roll inward	76.2 mm
Film roll O.D	240 mm